


XM-17M-VD24 relay - Voltage monitoring, Datasheet

1 C/O, 16 A



Description

When the voltage increases or decreases the relay will switch, depending of the set U_{min} and U_{max} . As well U_{min} as U_{max} can be monitored independently from each other.

A adjustable time delay can be set between 0 and 10 seconds to eliminate short voltage drops or peaks. The 3-state LED will give a indication depending of the status of the relay, normal state and 2 fault states.

Application

Monitoring voltage level in battery circuits 12 or 24 VDC. Serves to control supply voltage for appliances sensitive to supply tolerance, protection of the device against under- and overvoltages.

Features

- Measuring range 6...30 VDC
- Monitored voltage serves also as supply voltage
- 1 C/O contact 16 A / AC 1
- U_{max} and U_{min} can be monitored separately
- Adjustable time delay 0...10 s
- Inbuilt diode for suppressing peaks
- 35 mm rail mounting
- Output status by LED indicator
- Modular housing, 1 module

Benefits

- Rated current 16 A / AC1
- Long term availability
- 17.6 mm wide
- No maintenance

Industry compliancy


All our relays and accessories are designed according to regulations:

- EN 60255-6
- EN 61010-1
- CE

XM-17M-VD24 relay

Technical specifications

Connection diagram



Time range

Time ranges	Adjustable 0...10 s
Time setting	Potentiometer
Setting accuracy	5 %
Repeat accuracy	< 1 %

Output

Number of contacts	1x change-over contact / SPDT (AgNi/Silver alloy)
Rated current	16 A / AC1
Breaking capacity	4000 VA / AC1, 384 W / DC
Inrush current	30 A / < 3 s
Switching voltage	250 VAC1 / 24 VDC
Min. breaking capacity DC	500 mW
Output indication	Red / green LED
Mechanical life	30 x 10 ⁶ operations
Electrical life (AC1)	7 x 10 ⁴ operations

Supply and measuring


Supply measuring terminals	A1 - A2
Supply / measuring voltage	6...30 VDC
Burden	Max. 1.2 VA
Upper level (U _{max})	18...30 VDC
Bottom level (U _{min})	30 - 95 % U _{max}
Max. permanent	36 VAC
Peak overload	50 VAC



XM-17M-VD24 relay

Technical specifications

Connection



Environmental conditions

Operating temperature	-20 °C... +55 °C
Storage temperature	-30 °C... +70 °C
Electrical strength	4 kV (supply - output)
Operating position	Any
Mounting	35 mm rail EN 60715
Protection degree	IP40 front panel
Overtoltage category	III
Pollution degree	2
Max. cable size	Solid wire max. 1 x 2.5 mm ² or 2 x 1.5 mm ² / with sleeve max. 1 x 2.5 mm ²

Mechanical data


Dimensions (d x w x h)	90 x 17.6 x 64 mm
Weight	73 g




XM-17M-VD24 relay

Technical specifications

Description



Functions



LED indication



XM-17M-VD24 relay

Odering codes

Art. no.	Type	Function	Contacts	Voltage range
326001027	XM-17M-IA25U	AC 1-phase current monitoring	1 C/O	230 VAC 50/60 Hz
326002003	XM-17M-M400L	AC 3-phase voltage monitoring	1 C/O	3x 400 VAC 50 Hz
326002004	XM-17M-M400LN	AC 3-phase + N voltage monitoring	1 C/O	3x 400 VAC / 230 VAC 50 Hz
326002000	XM-17M-VA230	AC 1-phase voltage monitoring	1 C/O	48-276 VAC 50 Hz
326002002	XM-17M-2XVA230	AC 1-phase voltage monitoring	2x 1 C/O	48-276 VAC 50 Hz
326002011	XM-17M-VA400LN	AC 3-phase + N voltage monitoring	1 C/O	3x 400 VAC / 230 VAC 50 Hz
326002001	XM-17M-VD24	DC 1-phase voltage monitoring	1 C/O	6-30 VDC
326002006	XM-52M-M400L	AC 3-phase complete monitoring	2 C/O	230 VAC / 400 VAC 50/60 Hz
326002007	XM-52M-M400LN	AC 3-phase + N voltage monitoring	2 C/O	230 VAC / 400 VAC 50/60 Hz
326002005	XM-52M-VA500	AC/DC 1-phase voltage monitoring	2 C/O	10-500 VAC/DC 50 Hz





Mors Smitt France SAS

Tour Rosny 2, Avenue du Général de Gaulle,
F - 93118 Rosny-sous-Bois Cedex, FRANCE
T +33 (0)1 4812 1440, F +33 (0)1 4855 9001
E sales@msrelais.com

Mors Smitt Asia Ltd.

807, Billion Trade Centre, 31 Hung To Road
Kwun Tong, Kowloon, HONG KONG SAR
T +852 2343 5555, F +852 2343 6555
E info@morssmitt.hk

Mors Smitt B.V.

Vrieslantlaan 6, 3526 AA Utrecht,
NETHERLANDS
T +31 (0)30 288 1311, F +31 (0)30 289 8816
E sales.msbv@wabtec.com

Mors Smitt Technologies Inc.

1010 Johnson Drive,
Buffalo Grove, IL 60089-6918, USA
T +1 847 777 6497, F +1 847 520 2222
E salesmst@wabtec.com

Mors Smitt UK Ltd.

Doulton Road, Cradley Heath
West Midlands, B64 5QB, UK
T +44 (0)1384 567 755, F +44 (0)1384 567 710
E sales.msuk@wabtec.com